

63/70 COMBINED TANKS



63/70

The combined tanks are equipped with:
- side mounting kit

Mounting kit: available for side position.

OIL


- air breather cap h 41
- round aluminium level gauge 1" (specific indicator on the EVO Filter)
- adjustable ball valve

DIESEL OIL

- fuel cap with key and safety valve

Notes:

- Homologation ECE 34 Part III for diesel oil part
- Available on request the specific level indicator for the diesel oil part



63/70 (sidewalls 636 mm h x 706 mm w)

DIESEL OIL TANK	Products range	Bayonet connection	Level Indicator VDO	Side mounting kit	Diesel drenage	ECE 34 Part III	LT* Diesel/Oil	Dimensions L x H x W	Material	Product Code MF NSMA = Alu NSMF = Steel NSMI = Stainless steel	Product Code EVO NSMA = Alu NSMF = Steel NSMI = Stainless steel	
	Products range	Filter Flange	Level Indicator E = Spy eye L = Level gauge	Adjustable Ball Valve	Returns	Valve Plate						Mounting kit
DIESEL OIL TANK	Diesel oil tank	●	○	●	●	●	125/140	700 X 636 X 706	A/F/I	- 0125070C100	- 0125070CE00	
							140/170	800 X 636 X 706	A/F/I	- 0140080C100	- 0140080CE00	
OIL TANK							160/150	800 X 636 X 706	A/F/I	- 0160080C100	- 0160080CE00	
							180/170	900 X 636 X 706	A/F/I	- 0180090C100	- 0180090CE00	
							190/200	1000 X 636 X 706	A/F/I	- 0190100C100	- 0190100CE00	
							200/150	900 X 636 X 706	A/F/I	- 0200091C100	- 0200091CE00	
	Multi Function (MF)	● embossed 135	● E	● 1"1/2	●	●	● Side	220/170	1000 X 636 X 706	A/F/I	- 0220100C100	- 0220100CE00
								280/200	1250 X 636 X 706	A/F/I	- 0280125C100	- 0280125CE00
								380/200	1500 X 636 X 706	A/F/I	- 0380150C100	- 0380150CE00
	Evo (ET)	● Evo	● Part of Evo Filter	● 1"1/2	●	●	● Side	410/170	1500 X 636 X 706	A/F/I	- 0410150C100	- 0410150CE00
							600/200	2000 X 636 X 706	A/F/I	- 0600200C100	- 0600200CE00	

* Full tank capacity

● included ○ predisposed (not incl) ● not included in the standard tanks

Mounting specifics

A (mm)	Diesel full capacity (l)	Oil level indicator capacity (l)
700	120	126
800	140	143
800	160	126
900	180	143
1000	202	160
900	200	126
1000	220	143
1250	306	160
1500	409	160
1500	428	143
2000	616	160

